

TECHNICAL DATA SHEET | AUTOMOTIVE

Engen Xtreme 15W-40

Robust Crankcase Engine Oil Designed For Use In Older High Performance Motors



Description

Engen Xtreme 15W-40 is a high performance, mineral based, engine crankcase oil designed for use in modern petrol and diesel engines of cars, MPVs, SUVs and pick-ups, both naturally aspirated and turbocharged. It exceeds the requirements of and is formally approved against API Service Classifications SL/CF as well as meeting the A3 and B3 performance requirements of ACEA.

It exceeds major car manufacturer's engine oil performance requirements for service fill and top-up purposes. In addition to these standards Engen Xtreme 15W-40 meets a wide range of other specifications and performance criteria. It is formulated using low volatility base oils which contributes to reduced oil consumption. It contains a highly shear stable viscosity index improver which ensures "stay-in-grade" performance over its whole service life.

Benefits & Features

- Easier cold temperature starting
- Outstanding protection against wear and corrosion
- Excellent high temperature stability, detergency and protection
- Low pour point and high viscosity index for wide operating temperature range
- Extended engine life

Application

Engen Xtreme 15W-40 is recommended for use in most naturally aspirated and turbocharged petrol and diesel engines in cars, MPVs, SUVs and pick-ups, as well as for four stroke motorcycle engines fitted with a dry clutch design. It is approved by major engine manufacturers as a service fill and for top-up purposes under warranty conditions.

Being an SAE 15W-40 multigrade oil, it is suitable for use over a wide operating temperature range. Its high temperature stability, detergency and protection reserve keeps engine components clean and protected, thus reducing wear, ensuring long engine life over extended service intervals.

Performance Level

Meets or exceeds the following Industry Standards:

- API SL/CF
- ACEA A3-96/B3-96

Meets or Exceeds Approvals & Specifications:

- VW 501.01/505.00
- MB 229.1

With us you are Number One



Typical Physical Characteristics

ENGEN XTREME 15W-40			
PARAMETERS	METHODS	UNITS	TYPICAL VALUES
SAE No.	-	-	15W-40
Viscosity @ 40°C	ASTM D445	cSt	116
Viscosity @ 100°C	ASTM D445	cSt	15,3
Viscosity Index	ASTM D2270	-	133
Flash Point	ASTM D92	°C	222
Pour Point	ASTM D5950	°C	-33
Total Base No.	ASTM D2896	mgKOH/g	10,1
Sulphated Ash	ASTM D874	% m/m	1,0

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to Engen's specification, variations in these characteristics may occur.

11.2021

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil, or water. For further detail regarding storage, safe handling, and disposal of product, please refer to Product SDS. Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility shall be taken by either Engen or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representatives in the event you require any further information.

For more information about this product and other products in our range please scan the following:



+27 8600 36436